

【Note】

- *1 Status monitoring can be performed for devices that conform to RFC1759.
- *2 Unable to use Internet Fax(SIP).
- *3 Controller ROM 2.100.3 and above is ○
- *4 Controller ROM 1.121.14 and above or 1.122.18 and above is ○
- *5 Controller ROM 1.104.1 and above is ○
- *6 Controller ROM 1.180.4 and above is ○
- *7 Controller ROM 1.180.2 and above is ○
- *8 Controller ROM 1.103.x and above is ○
- *9 Controller ROM 1.100.1 and above is ○
- *10 Printer-related features cannot be used.
- *11 1.1.0.1 or later is required to use ApeosWare Print Management.
- *12 Controller ROM 1.101.20 and above is ○
- *13 Controller ROM 3.120.13 and above is ○
- *14 Controller ROM 1.120.40 and above is ○
- *15 Controller ROM 1.103.13 and above is ○
- *16 Only PCL driver is supported (Mini driver is not supported.)
- *17 Controller ROM 1.3.04 and above is ○
- *18 Controller ROM 1.101.12 and above is ○
- *19 Controller ROM 1.0.25 and above is ○
- *20 Controller ROM 2.0.0 and above is ○
- *21 Print via print-server cannot be used.
- *22 OCR feature cannot be used.
- *23 You will need Network Scanner Utility 2 to retrieve document.
- *24 You cannot select account. Cost is reduced from the default account.
- *25 An Option may be required according to type or model.
- *26 Available only in Direct Print mode via ApeosWare Management Suite 2 and print feature using On Demand Print Terminal.
For a print job that has reached the minimum balance when printing, the print job is canceled in the case of Direct Print mode, and printing cannot be started on the On Demand Print Terminal.
However, "On Demand Print Terminal" option must be available to use it. "On Demand Print Terminal" is an option for the Japanese domestic market.
- *27 Authentication Controller cannot be available. Please use the optional IC Card reader.
- *28 Controller ROM Ver.201802150951 and above is ○
- *29 Controller ROM Ver.201802270653 and above is ○
- *30 Controller ROM Ver.201802270642 and above is ○
- *31 HDD required

For this software, CentreWare Internet Services and device configuration reports, the following models will be recorded as "Fuji Xerox 4112" or "Fuji Xerox 4127".

4112
4112 Light Publisher
4127 Light Publisher

For this software, CentreWare Internet Services and device configuration reports, the following models will be recorded as "Fuji Xerox D95", "Fuji Xerox D110", "Fuji Xerox D125" or "Fuji Xerox D136".

D95
D110
D110 Light Publisher
D125 Light Publisher
D136

You can check the device's Controller ROM version on its control panel.

Click the [Machine Status] button, select [General Information] on the [Machine Information] screen and check [Software Version].

You can also check the version on the printed device configuration reports

For devices with "Large Color Control Panel", the Controller ROM version displayed with the above methods will be displayed as follows.

- Display on Device: 1.120.xx -> 1.100
- Display on Device: 1.121.xx -> 1.101
- Display on Device: 1.122.xx -> 1.102

When [Local Authentication/Local Accounting (Local Authentication)] or [Local Authentication/Network Accounting (Network Authentication)] is selected in administration site settings for the following models, the Card ID of the smart card can be specified in [Alternate Authentication ID] of User Information.

To check the card information of the smart card against the User ID of the device, device configuration is required. Refer to the device manual for details.

- ApeosPort-V C7775/C6675/C5575/C4475/C3375/C3373/C2275
- ApeosPort-V C7780/C6680/C5580
- ApeosPort-IV C5575/C4475/C3375/C3373/C2275
- ApeosPort-IV 7080/6080
- ApeosPort-IV 5070/4070/3070
- ApeosPort-IV C7780/C6680/C5580
- ApeosPort-IV C4430
- ApeosPort-IV C5570/C4470/C3370/C3371/C2270 ※1
- ApeosPort-III C7600/C6500/C5500 ※2
- Fuji Xerox D136
- Fuji Xerox D95/D110/D125
- Fuji Xerox 4112 / 4127 (ControllerROM Ver 1.10) ※3
- DocuCentre-V C7775/C6675/C5575/C4475/C3375/C3373/C2275
- DocuCentre-V C7780/C6680/C5580
- DocuCentre-IV C2265/C2263
- DocuCentre-IV C5575/C4475/C3375/C3373/C2275
- DocuCentre-IV 7080/6080
- DocuCentre-IV 5070/4070
- DocuCentre-IV 3065/3060/2060
- DocuCentre-IV C7780/C6680/C5580
- DocuCentre-IV C4430
- DocuColor 1450 GA
- DocuCentre-IV C5570/C4470/C3370/C3371/C2270 ※1
- DocuCentre-IV C2260 ※4
- DocuCentre-III C7600/C6500/C5500 ※2
- DocuPrint 3105
- DocuPrint CM505 da
- DocuPrint C5005 d

The versions supported by [Local Authentication/Network Accounting (Network Authentication)] are as follow:

- ※1 Controller ROM 1.101.15 and above
- ※2 Controller ROM 3.120.9 and above
- ※3 Controller ROM 1.111.6 and above
- ※4 Controller ROM 1.120.31 and above

When [Remote Authentication] is selected for administration site settings, the versions of the devices supported in ApeosWare Authentication Management are as follows.

- ApeosPort-IV C5570/C4470/C3370/C3371/C2270 ※1
- ApeosPort-III C7600/C6500/C5500 ※2
- ApeosPort-III C4400 ※3
- ApeosPort-III C3300/C2200/C2201 ※4
- Fuji Xerox 4112 / 4127 (Controller ROM Ver 1.10) ※5
- DocuPrint C2255 ※6

- ※1 Controller ROM 1.103.4 or below
- ※2 Controller ROM 3.120.9 or below
- ※3 Controller ROM 1.121.111 or below
- ※4 Controller ROM 1.120.111 or below
- ※5 Controller ROM 1.111.6 or below
- ※6 Controller ROM 1.100.26 or below